

## 2021 New Buzzer Models

Sr. No.	Model	Tone	Sound level at 30cm for 12Vdc (+/-10dB)	Operating Voltage/ input	Max. Current mA	Capsule Dimension (L*H mm)
<b>New Die- 9mm Height Capsule</b>						
1	SB20-C	Continuous	85dB	6 to 24Vdc	28	23.5*9
2	SB27-C	Continuous	85dB	6 to 24Vdc	28	30.0*9
4	SB20-I	Intermittent	85dB	6 to 24Vdc	25	23.5*9
5	SB27-I	Intermittent	85dB	6 to 24Vdc	25	30.0*9
6	B20R	ringer	85dB	30 Vpp Max	NA	23.5*9
7	B20RF	ringer	85dB	30 Vpp Max	NA	23.5*9
8	B27R	ringer	85dB	30 Vpp Max	NA	30.0*9
9	B27RF	ringer	85dB	30 Vpp Max	NA	30.0*9
<b>New Die-27mm Capsule with 5.5mm sounding hole</b>						
10	L27C-M-12V	Continuous	105dB	6 to 18Vdc	20	31.9*20.5
<b>New Die-40mm Capsule</b>						
11	L40C-12V	Continuous	105dB	6 to 18Vdc	20	40.0*19.5

<b>Mounting</b>	<b>Wire / lead length</b>	<b>Pitch</b>	<b>Material</b>	<b>Frequency (+/-500hz)</b>	<b>Type</b>
PCB mounting	9mm(+/-1mm)	11mm	ABS	4kz	Self Drive
PCB mounting	9mm(+/-1mm)	17.2mm	ABS	4kz	Self Drive
PCB mounting	9mm(+/-1mm)	11mm	ABS	4kz	Self Drive
PCB mounting	9mm(+/-1mm)	17.2mm	ABS	4kz	Self Drive
2 wire or pin type	9mm(+/-1mm) OR 120mm wire	11mm	ABS	4kz	External Drive
3 wire	120mm wire	29mm	ABS	4kz	External Drive
2wire OR pin type	9mm(+/-1mm) OR 120mm wire	17.2mm	ABS	4kz	External Drive
3 wire	120mm wire	36mm	ABS	4kz	External Drive
2 pin connector 110mm PVC sleeve 3mm, Vinay Auto 3622 TLB2814	120mm wire	37.14mm	Nylon-6	4kz	Self Drive
wire Type	150mm wire (+/-10mm)	50.0mm	Nylon-6	4kz	Self Drive